

CLEAN VERSION OF AMENDED CLAIMS

A¹ 1. (Amended) During formation of a concrete wall, a device for supporting a weldment plate, said device comprising:

an elongate body portion having a length substantially equal to the thickness of the concrete wall minus a dimension of the weldment plate extending in a direction of the thickness of the concrete wall;

a surface engaging portion for contacting a surface on which the concrete wall is poured and supporting the weldment plate in a position appropriately spaced from that surface;

and

means for attaching said elongate body portion to the weldment plate,

wherein the device is capable of maintaining the weldment plate in a desired position as wet concrete is poured and sets up.

2. (Amended) The device of Claim 1, wherein said length of said elongate body portion is adjustable.

A² 4. (Amended) The device of Claim 2, wherein said elongate body portion comprises two components which may be adjusted relative to each other to achieve the desired length.

A³ 6. (Amended) The device of Claim 4, wherein said means for attaching said elongate body portion to the weldment plate comprises an adhesive layer between said weldment plate and one of said components.

A⁴ 9. (Amended) The device of Claim 1, wherein the weldment plate includes a plate member and projections extending from the plate member, said means for attaching said elongate

A4
cont

body portion to the weldment plate further comprising means for securing said device to a head portion of the weldment projection.

10. (Amended) The device of Claim 9, wherein the projections are Nelson studs welded to the nether side of the plate member and said means for securing said device to the head portion of the weldment projections further comprising a plurality of fingers to capture the head portion of the Nelson stud securing said device thereto.

NEW CLAIMS 12-30

A⁵ 12. During formation of a concrete wall, a device for supporting a weldment plate, the device comprising:

an elongate body portion having a length substantially equal to the thickness of the concrete wall minus a dimension of the weldment plate extending in a direction of the thickness of the concrete wall;

a surface engaging portion for contacting a surface on which the concrete wall is poured and supporting the weldment plate in a position appropriately spaced from that surface;

the length of said elongate body portion being adjustable;

said elongate body portion comprising two components which may be adjusted relative to each other to achieve the desired length;

said two components being threadably engaged and rotation of one component relative to a second component results in a change in the length of said elongate body portion; and

means for attaching said elongate body portion to the weldment plate,

wherein the device is capable of maintaining the weldment plate in a desired position as wet concrete is poured and sets up.

13. The device according to Claim 12, wherein said means for attaching said elongate body portion to the weldment plate comprises an adhesive layer between said weldment plate and one of said components.

3 14. The device according to Claim 12, wherein said surface engaging portion comprises a section which tapers to a point to minimize surface treatment of the concrete wall needed to accommodate said device.

AS
Cont

4
15

The device according to Claim ~~12~~¹, wherein a material for said device is selected from a group consisting of plastic, metal and powdered metal.

5
16

The device according to Claim ~~12~~¹, wherein the weldment plate includes a plate member and projections extending from the plate member, said means for attaching said elongate body portion to the weldment plate further comprising means for securing said device to a head portion of the weldment projection.

6
17

The device according to Claim ~~16~~⁵, wherein the projections are Nelson studs welded to the nether side of the plate member and said means for securing said device to the head portion of the weldment projections comprising a plurality of fingers to capture the head portion of the Nelson stud securing said device thereto.

Sub 1

~~18. The device according to Claim 17, wherein said plurality of fingers comprises at least three equally spaced fingers with portions that snap behind the head portion of the weldment projection.~~

8
19

During formation of a concrete wall, a device for supporting a weldment plate, said device comprising:

an elongate body portion having a length substantially equal to the thickness of the concrete wall minus a dimension of the weldment plate extending in a direction of the thickness of the concrete wall;

a surface engaging portion for contacting a surface on which the concrete wall is poured and supporting the weldment plate in a position appropriately spaced from that surface;

the length of said elongate body portion being adjustable;

said elongate body portion comprising two components which may be adjusted relative to each other to achieve the desired length; and

AS
cont means for attaching said elongate body portion to the weldment plate, said means
for attaching comprising an adhesive layer between said weldment plate and one of said
components,

wherein the device is capable of maintaining the weldment plate in a desired position
as wet concrete is poured and sets up.

~~20~~⁹ The device according to Claim ~~19~~⁸, wherein said two components are threadably
engaged and rotation of one component relative to a second component results in a change in the
length of said body portion.

~~21~~¹⁰ The device according to Claim ~~19~~⁸, wherein said surface engaging portion
comprises a section which tapers to a point to minimize surface treatment of the concrete wall
needed to accommodate said device.

~~22~~¹¹ The device according to Claim ~~19~~⁸, wherein a material for said device is selected
from a group consisting of plastic, metal and powdered metal.

~~23~~¹⁸ During formation of a concrete wall, a device for supporting a weldment plate,
said device comprising:

an elongate body portion having a length substantially equal to the thickness of the
concrete wall minus a dimension of the weldment plate extending in a direction of the thickness of
the concrete wall;

a surface engaging portion for contacting a surface on which the concrete wall is
poured and supporting the weldment plate in a position appropriately spaced from that surface;

means for attaching said elongate body portion to the weldment plate;

AS
cont

the weldment plate comprising a plate member and projections extending from the plate member, said means for attaching said elongate body portion to the weldment plate further comprising means for securing said device to a head portion of the weldment projection; and

the projections being Nelson studs welded to the nether side of the plate member and said means for securing said device to a head portion of the weldment projection further comprising a plurality of fingers to capture the head portion of the Nelson stud securing said device thereto,

wherein the device is capable of maintaining the weldment plate in a desired position as wet concrete is poured and sets up

~~Sub B~~ 24. The device according to Claim 23, wherein said plurality of fingers comprises at least three equally spaced fingers with portions that snap behind the head portion of the weldment projection.

14
25. The device according to Claim 24, wherein said length of said elongate body portion is adjustable.

15
26. The device according to Claim 25, wherein said length is adjustable by manually removing excess length.

16
27. The device according to Claim 25, wherein said elongate body portion comprises two components which may be adjusted relative to each other to achieve the desired length.

17
28. The device according to Claim 27, wherein said two components are threadably engaged and rotation of one component relative to a second component results in a change in the length of said elongate body portion.

AS
cont

~~29~~¹⁸

The device according to Claim ~~23~~¹², wherein said surface engaging portion comprises a section which tapers to a point to minimize surface treatment of the concrete wall needed to accommodate said device.

~~30~~¹⁹

The device according to Claim ~~23~~¹², wherein a material for said device is selected from a group consisting of plastic, metal and powdered metal.
